



DÜŞÜK BASINÇ DİYAFRAMLI Püskürtme Seti

K40

dermix®

Low Pressure Diaphragm Spraying Set

TEKNİK ÖZELLİKLER Technical Properties

ÇALIŞMA BASINCI	Working Pressure	: 1 - 8 bar
SIVI BASINCI	Fluid Pressure	: 1 - 8 bar
MAKSİMUM DEBİ	Maximum Flow	: 40 litre/dakika
POMPA ÇIKIŞI	Pump Output	: 3/8"
HAVA GİRİŞİ	Air Input	: 1/4"
DİYAFRAM	Diaphragm	: Teflon
AĞIRLIK	Weight	: 7 kg
GÖVDE	Body	: Alüminyum

KULLANIM ALANLARI Applications

- AHŞAP BOYAMA Wood Painting
- DOLGU UYGULAMALARI Filling Application
- VERNİK UYGULAMALARI Varnish Application
- METAL BOYAMA Metal Painting
- YAPIŞTIRICI PÜSKÜRME Adhesive Spraying
- YAĞLAMA SİSTEMLERİ Lubrication Systems
- SOĞUTMA SİSTEMLERİ Cooling Systems
- MANUEL PÜSKÜRTME SİSTEMLERİ Manual Spray Systems

