

ST200-P

BASINÇLI TABANCA
Pressure Gun



TEKNİK ÖZELLİKLER

Technical Properties

ÇALIŞMA BASINCI	Working Pressure	: 3 bar
HAVA GİRİŞİ	Air Input	: 1/4"
PÜSKÜRTME AÇISI	Spraying Angle	: 250-280 mm
HAVA TÜKETİMİ	Air Consumption	: 110-170 lt/dk
HAVA AYARI	Air Setting	: Var
AĞIRLIK	Weight	: 483 gr
İĞNE SEÇENEKLERİ	Needle Options	: 1.1 - 1.3 - 1.5 - 1.8 2.0 - 2.5 mm

ST200-S

ALT DEPO TABANCA
Suction Gun



TEKNİK ÖZELLİKLER

Technical Properties

ÇALIŞMA BASINCI	Working Pressure	: 3 bar
HAVA GİRİŞİ	Air Input	: 1/4"
DEPO HACMİ	Tank Capacity	: 1000 cc
PÜSKÜRTME AÇISI	Spraying Angle	: 250-280 mm
HAVA TÜKETİMİ	Air Consumption	: 150-180 lt/dk
HAVA AYARI	Air Setting	: Var
AĞIRLIK	Weight	: 820 gr
İĞNE SEÇENEKLERİ	Needle Options	: 1.1 - 1.3 - 1.5 - 1.8 2.0 - 2.5 mm

ST400

ÜST DEPO TABANCA
Gravity Gun



TEKNİK ÖZELLİKLER

Technical Properties

ÇALIŞMA BASINCI	Working Pressure	: 3 bar
HAVA GİRİŞİ	Air Input	: 1/4"
DEPO HACMİ	Tank Capacity	: 600 cc
PÜSKÜRTME AÇISI	Spraying Angle	: 250-280 mm
HAVA TÜKETİMİ	Air Consumption	: 150-180 lt/dk
HAVA AYARI	Air Setting	: Var
AĞIRLIK	Weight	: 590 gr
İĞNE SEÇENEKLERİ	Needle Options	: 1.1 - 1.3 - 1.5 - 1.8 2.0 - 2.5 mm